

## **ANUCRYL C-333**

### **TECHNICAL DATA SHEET**

INTRODUCTION

ANUCRYL C-333 is a pure acrylic emulsion. It has UV and water resistance with strong adhesion property. It gives hard, clear and

glossy film.

**APPLICATION** 

ANUCRYL C-333 is used in high glossy exterior and interior

emulsion paints.

Appearance : Milky white liquid.

% Solid Content :  $50 \pm 1$  pH (As is) : 8.5 - 10.5

TYPICAL PROPERTIES Brook Field Viscosity

Spindle no. 2/ RPM 30 @ 30°C : 200 (max) Cps

Glass Transition Temperature

Theoretical Tg [°C] : 22

Film properties : Clear Transparent, UV Resistant

SAFETY DATA

Health Hazard: ANUCRYL C-333 is alkaline in nature and harmful if swallowed. Avoid contact with skin. Use protective clothing, hand gloves, goggles, safety shoes etc., while handling. In case of contact or splash on eyes, wash with sufficient amount of water and consult a

physician.

Fire Hazard: ANUCRYL C-333 is water based and non-flammable.

STORAGE Sto

Store products in tightly closed original containers at temperatures recommended on the product label.

PACKAGING 240 Kg HDPE Drums/Tanker.

# HANDLING PRECAUTION

Before using this product, consult the Material Safety Data Sheet (MSDS) for details on product hazards, recommended handling precautions and product storage.

#### DISCLAIMER

This information is given to the best of our knowledge. There is no legally binding assurance of certain properties for a specific purpose. The customer is responsible for determining whether the product and Information provided here is appropriate for his use or not. It is the sole responsibility of the customer to ensure that any proprietary rights and existing laws and legislation are observed.

### ANUVI CHEMICALS LIMITED (AN ISO 9001: 2015 COMPANY)

**Sales office:** 205/210/211, Narmada, Laxmi Industrial Premises, Pokharan Road No.1, Vartak Nagar, Thane [w] - 400 606,

Maharashtra, India.

**Tel.**: +91-22-25855379 / 25855714 **Website** <u>www.anuvi.in</u>

