



ANUCRYL C-355

TECHNICAL DATA SHEET

INTRODUCTION	<p>ANUCRYL C-355 is a pure acrylic emulsion. It has excellent exterior durability, outstanding adhesion and UV resistance. It has good water resistance and high gloss due to very fine particle size of the emulsion. It provides excellent scrub resistance.</p>																		
APPLICATION	<p>ANUCRYL C-355 is used for Premium high sheen interior and exterior emulsion paints.</p>																		
TYPICAL PROPERTIES	<table><tr><td>Appearance</td><td>:</td><td>Bluish white liquid.</td></tr><tr><td>% Solid Content</td><td>:</td><td>55 ± 1</td></tr><tr><td>pH(as is)</td><td>:</td><td>9-10</td></tr><tr><td>Brookfield viscosity</td><td>:</td><td>200 [max] Cps</td></tr><tr><td>Spindle No.1 /RPM 30 @ 30°C</td><td>:</td><td></td></tr><tr><td>Film Properties</td><td>:</td><td>Clear</td></tr></table>	Appearance	:	Bluish white liquid.	% Solid Content	:	55 ± 1	pH(as is)	:	9-10	Brookfield viscosity	:	200 [max] Cps	Spindle No.1 /RPM 30 @ 30°C	:		Film Properties	:	Clear
Appearance	:	Bluish white liquid.																	
% Solid Content	:	55 ± 1																	
pH(as is)	:	9-10																	
Brookfield viscosity	:	200 [max] Cps																	
Spindle No.1 /RPM 30 @ 30°C	:																		
Film Properties	:	Clear																	
SAFETY DATA	<p>Health Hazard: ANUCRYL C-355 is alkaline in nature and harmful if swallowed. Avoid contact with skin. Use protective clothing, hand gloves, goggles, safety shoes etc., while handling this material. In case of contact or splash on eyes, wash with sufficient amount of water and consult a physician.</p> <p>Fire Hazard: ANUCRYL C-355 is water-based and non-flammable.</p>																		
STORAGE	<p>Store products in tightly closed original containers at temperatures recommended on the product label.</p>																		
PACKAGING	<p>240 Kg HDPE Drums/Tanker.</p>																		

**HANDLING
PRECAUTION**

Before using this product, consult the Material Safety Data Sheet (MSDS) for details on product hazards, recommended handling precautions and product storage.

DISCLAIMER

This information is given to the best of our knowledge. There is no legally binding assurance of certain properties for a specific purpose. The customer is responsible for determining whether the product and Information provided here is appropriate for his use or not. It is the sole responsibility of the customer to ensure that any proprietary rights and existing laws and legislations are observed.

ANUVI CHEMICALS LIMITED (AN ISO 9001: 2015 COMPANY)

Sales office: 205/210/211, Narmada, Laxmi Industrial Premises,
Pokharan Road No.1, Vartak Nagar, Thane (W) - 400 606,
Maharashtra, India.

Tel.: +91-22-25855379 / 25855714 **Website** www.anuvi.in

