

ANUCRYL K-5800

TECHNICAL DATA SHEET

INTRODUCTION

ANUCRYL K-5800 is a pure acrylic emulsion. It has good durability,

adhesion and gloss. It is UV resistant.

APPLICATION

TYPICAL PROPERTIES

ANUCRYL K-5800 is used in Medium Glossy Exterior and Interior Paints. The film formed from ANUCRYL K-5800 dries up quickly and

can be easily applied by brush, spray or roller application.

Appearance

Milky white liquid

% Solids Content

50 ± 1

Brook Field Viscosity

Spindle no. 3/ RPM 60@ 30°c

250 (max) Cps 8.5 – 10.5

pH (As is)

Glass Transition Temperature

Theoretical Tg [°C]

19

Film properties

: Clear transparent

SAFETY DATA

Health Hazard: ANUCRYL K-5800 is alkaline in nature and harmful if swallowed. Avoid contact with skin. Use protective clothing, hand gloves, goggles, safety shoes etc., while handling this material. In case of contact or splash on eyes, wash with copious amount of water and

consult a physician.

Fire Hazard: ANUCRYL K-5800 is a water-based and non-flammable

STORAGE

Store products in tightly closed original containers at temperatures

recommended on the product label.

PACKAGING	240 Kg HDPE Drums/Tanker.
-----------	---------------------------

HANDLING PRECAUTION

Before using this product, consult the Material Safety Data Sheet (MSDS) for details onproduct hazards, recommended handling precautions and product storage.

DISCLAIMER

This information is given to the best of our knowledge. There is no legally binding assurance of certain properties for a specific purpose. The customer is responsible for determining whether the product and Information provided here is appropriate for his use or not. It is the sole responsibility of the customer to ensure that any proprietary rights and existing laws and legislation are observed.

ANUVI CHEMICALS LIMITED (AN ISO 9001: 2015 COMPANY)

Sales office: 205/210/211, Narmada, Laxmi Industrial Premises, Pokharan Road No.1, Vartak Nagar, Thane (W) - 400 606,

Maharashtra, India.

Tel.: +91-22-25855379 / 25855714 **Website** <u>www.anuvi.in</u>

