

ANUCRYL C-550A

2000 - 4000 Cps

TECHNICAL DATA SHEET

INTRODUCTION

ANUCRYL C-550A is a styrene/ acrylic emulsion. It is ecofriendly, Formaldehyde and APEO free. It is specially designed for paints having high PVC loading and excellent abrasion resistance. It has excellent water and alkali resistance.

APPLICATION

ANUCRYL C-550A is used for Economic Emulsion Paints, Texture paints and Flexible Coatings.

TYPICAL PROPERTIES

Appearance : Milky white liquid

% Solid Content : 50 ± 1 pH : 8.0 - 10.0

Brook Field Viscosity

Spindle no. 3/ RPM 20@ 30°C

Glass Transition Temperature

Theoretical Tg [°C] : 21
Film Properties : Clear

SAFETY DATA

Health Hazard: ANUCRYL C-550A is alkaline in nature and harmful if swallowed. Avoid contact with skin. Use protective clothing, hand gloves, goggles, safety shoes etc., while handling this material. In case of contact or splash on eyes, wash with enough water and consult a physician.

Fire Hazard: ANUCRYL C-550A is water-based and non-flammable.

STORAGE

Store products in tightly closed original containers at temperatures recommended on the product label.

PACKAGING

240 Kg HDPE Drums/Tanker.

HANDLING PRECAUTION

Before using this product, consult the Material Safety Data Sheet (MSDS) for details on product hazards, recommended handling precautions and product storage.

DISCLAIMER

This information is given to the best of our knowledge. There is no legally binding assurance of certain properties for a specific purpose. The customer is responsible for determining whether the product and Information provided here is appropriate for his use or not. It is the sole responsibility of the customer to ensure that any proprietary rights and existing laws and legislation are observed.

ANUVI CHEMICALS LIMITED (AN ISO 9001: 2015 COMPANY)

Sales office: 205/210/211, Narmada, Laxmi Industrial Premises, Pokharan Road No.1, Vartak Nagar, Thane (W) - 400 606, Maharashtra, India.

anuvi

Tel.: +91-22-25855379 / 25855714 **Website** www.anuvi.in