

ANUCRYL C-60

TECHNICAL DATA SHEET

INTRODUCTION	ANUCRYL C-60 is a VAM / acrylic emulsion which has excellent flow and leveling with good brushability. It also has excellent mechanical stability. It also shows excellent adhesion to paper substrate and concrete substrate.												
APPLICATION	ANUCRYL C-60 is used for Premium Quality Interior Emulsion Paints.												
TYPICAL PROPERTIES	<table border="0"> <tr> <td>Appearance</td> <td>: Milky white liquid</td> </tr> <tr> <td>% Solid Content</td> <td>: 55 ± 1</td> </tr> <tr> <td>Brook Field Viscosity, Spindle no. 4/ RPM 12@ 30°C</td> <td>: 2000 – 6000 Cps</td> </tr> <tr> <td>Glass Transition Temperature Theoretical Tg [°C]</td> <td>: 20</td> </tr> <tr> <td>pH (As is)</td> <td>: 4.0 – 6.0</td> </tr> <tr> <td>Film Properties</td> <td>: Clear</td> </tr> </table>	Appearance	: Milky white liquid	% Solid Content	: 55 ± 1	Brook Field Viscosity, Spindle no. 4/ RPM 12@ 30°C	: 2000 – 6000 Cps	Glass Transition Temperature Theoretical Tg [°C]	: 20	pH (As is)	: 4.0 – 6.0	Film Properties	: Clear
Appearance	: Milky white liquid												
% Solid Content	: 55 ± 1												
Brook Field Viscosity, Spindle no. 4/ RPM 12@ 30°C	: 2000 – 6000 Cps												
Glass Transition Temperature Theoretical Tg [°C]	: 20												
pH (As is)	: 4.0 – 6.0												
Film Properties	: Clear												
SAFETY DATA	<p>Health Hazard: ANUCRYL C-60 is acidic in nature and harmful if swallowed. Avoid contact with skin. Use protective clothing, hand gloves, goggles, safety shoes etc., while handling this material. In case of contact or splash on eyes, wash with enough water and consult a physician.</p> <p>Fire Hazard: ANUCRYL C-60 is water-based and non-flammable.</p>												
STORAGE	Store products in tightly closed original containers at temperatures recommended on the product label.												
PACKAGING	240 Kg HDPE Drums/ Tanker.												

**HANDLING
PRECAUTION**

Before using this product, consult the Material Safety Data Sheet (MSDS) for details on product hazards, recommended handling precautions and product storage.

DISCLAIMER

This information is given to the best of our knowledge. There is no legally binding assurance of certain properties for a specific purpose. The customer is responsible for determining whether the product and Information provided here is appropriate for his use or not. It is the sole responsibility of the customer to ensure that any proprietary rights and existing laws and legislation are observed.

ANUVI CHEMICALS LIMITED (AN ISO 9001: 2015 COMPANY)

Sales office: 205/210/211, Narmada, Laxmi Industrial Premises,
Pokharan Road No.1, Vartak Nagar, Thane (W) - 400 606,
Maharashtra, India.

Tel.: +91-22-25855379 / 25855714 **Website** www.anuvi.in

