

ANUCRYL C-610

TECHNICAL DATA SHEET

INTRODUCTION	<p>ANUCRYL C-610 is a VAM / VeoVa emulsion which has excellent water resistance, dirt pick up resistance, mechanical stability and alkali resistance, as well as UV resistance. These vinyl versatate latexes display a good balance of performance properties</p>														
APPLICATION	<p>ANUCRYL C-610 is used for exterior textured coatings. It is recommended for use in interior and exterior flat and low sheen architectural coatings.</p>														
TYPICAL PROPERTIES	<table border="0"> <tr> <td>Appearance</td> <td>: Milky white liquid</td> </tr> <tr> <td>% Solid Content</td> <td>: 53± 1</td> </tr> <tr> <td>Brook Field Viscosity, # Spindle no. 4/ RPM 12</td> <td>: 2000 – 5000 Cps</td> </tr> <tr> <td>Glass Transition Temperature</td> <td></td> </tr> <tr> <td>Theoretical Tg [°C]</td> <td>: 19</td> </tr> <tr> <td>pH (As is)</td> <td>: 4.0 – 6.0</td> </tr> <tr> <td>Film Properties</td> <td>: Clear</td> </tr> </table>	Appearance	: Milky white liquid	% Solid Content	: 53± 1	Brook Field Viscosity, # Spindle no. 4/ RPM 12	: 2000 – 5000 Cps	Glass Transition Temperature		Theoretical Tg [°C]	: 19	pH (As is)	: 4.0 – 6.0	Film Properties	: Clear
Appearance	: Milky white liquid														
% Solid Content	: 53± 1														
Brook Field Viscosity, # Spindle no. 4/ RPM 12	: 2000 – 5000 Cps														
Glass Transition Temperature															
Theoretical Tg [°C]	: 19														
pH (As is)	: 4.0 – 6.0														
Film Properties	: Clear														
SAFETY DATA	<p>Health Hazard: ANUCRYL C-610 is acidic in nature and harmful if swallowed. Avoid contact with skin. Use protective clothing, hand gloves, goggles, safety shoes etc., while handling this material. In case of contact or splash on eyes, wash with enough water and consult a physician.</p> <p>Fire Hazard: ANUCRYL C-610 is water-based and non-flammable.</p>														
STORAGE	<p>Store products in tightly closed original containers at temperatures recommended on the product label.</p>														
PACKAGING	<p>240 Kg HDPE Drums/Tanker.</p>														

**HANDLING
PRECAUTION**

Before using this product, consult the Material Safety Data Sheet (MSDS) for details on product hazards, recommended handling precautions and product storage.

DISCLAIMER

This information is given to the best of our knowledge. There is no legally binding assurance of certain properties for a specific purpose. The customer is responsible for determining whether the product and Information provided here is appropriate for his use or not. It is the sole responsibility of the customer to ensure that any proprietary rights and existing laws and legislation are observed.

ANUVI CHEMICALS LIMITED (AN ISO 9001: 2015 COMPANY)

Sales office: 205/210/211, Narmada, Laxmi Industrial Premises,
Pokharan Road No.1, Vartak Nagar, Thane (W)- 400 606,
Maharashtra, India.

Tel.: +91-22-25855379 / 25855714 **Website** www.anuvi.in

