

ANUCRYL C-763

TECHNICAL DATA SHEET

INTRODUCTION

ANUCRYL C-763 is a Styrene/ Acrylic Emulsion. It is ecofriendly, formaldehyde and APEO free. It provides excellent stable

dispersion to colour gel particles in multi colour paints.

ANUCRYL C-763 is used for Base coat and continuous phase of **APPLICATION**

Multi Colour Paints.

Appearance Milky white liquid

% Solid Content 45 <u>+</u> 1 7.0 - 9.0рН

Brook Field Viscosity #5 **PROPERTIES**

TYPICAL

& Rpm 60@ 30°C 500 (max) Cps

Glass Transition Temperature

Theoretical Tg [°C] 12 Film Properties Clear

swallowed. Avoid contact with skin. Use protective clothing, hand **SAFETY DATA**

gloves, goggles, safety shoes etc., while handling this material. In case of contact or splash on eyes, wash with sufficient amount of water

Health Hazard: ANUCRYL C-763 is alkaline in nature and harmful if

and consult a physician.

Fire Hazard: ANUCRYL C-763 is water-based and non-flammable.

Store products in tightly closed original containers at temperatures **STORAGE**

recommended on the product label.

PACKAGING 240 Kg HDPE Drums/Tanker.

HANDLING PRECAUTION

Before using this product, consult the Material Safety Data Sheet (MSDS) for details on product hazards, recommended handling precautions and product storage.

DISCLAIMER

This information is given to the best of our knowledge. There is no legally binding assurance of certain properties for a specific purpose. The customer is responsible for determining whether the product and Information provided here is appropriate for his use or not. It is the sole responsibility of the customer to ensure that any proprietary rights and existing laws and legislation are observed.

ANUVI CHEMICALS LIMITED (AN ISO 9001: 2015 COMPANY)

Sales office: 205/210/211, Narmada, Laxmi Industrial Premises, Pokharan Road No.1, Vartak Nagar, Thane (W) - 400 606, Maharashtra, India.

Tel.: +91-22-25855379 / 25855714 **Website** <u>www.anuvi.in</u>

