

ANUCRYL C-764

TECHNICAL DATA SHEET

INTRODUCTION	ANUCRYL C-764 is a Pure Acrylic Emulsion. It is ecofriendly, formaldehyde and APEO free. It provides excellent stable dispersion to colour gel particles in multi-colour paints. It has excellent UV and water resistance.																					
APPLICATION	ANUCRYL C-764 is used for Base coat and continuous phase of Multi Colour Paints for interior and exterior application.																					
TYPICAL PROPERTIES	<table border="0"> <tr> <td>Appearance</td> <td>:</td> <td>Milky white liquid</td> </tr> <tr> <td>% Solid Content</td> <td>:</td> <td>45 ± 1</td> </tr> <tr> <td>pH</td> <td>:</td> <td>7.0 – 9.0</td> </tr> <tr> <td>Brook Field Viscosity #5 & Rpm 60@ 30°C</td> <td>:</td> <td>500 (max) Cps</td> </tr> <tr> <td>Glass Transition Temperature</td> <td>:</td> <td></td> </tr> <tr> <td>Theoretical Tg [°C]</td> <td>:</td> <td>12</td> </tr> <tr> <td>Film Properties</td> <td>:</td> <td>Clear</td> </tr> </table>	Appearance	:	Milky white liquid	% Solid Content	:	45 ± 1	pH	:	7.0 – 9.0	Brook Field Viscosity #5 & Rpm 60@ 30°C	:	500 (max) Cps	Glass Transition Temperature	:		Theoretical Tg [°C]	:	12	Film Properties	:	Clear
Appearance	:	Milky white liquid																				
% Solid Content	:	45 ± 1																				
pH	:	7.0 – 9.0																				
Brook Field Viscosity #5 & Rpm 60@ 30°C	:	500 (max) Cps																				
Glass Transition Temperature	:																					
Theoretical Tg [°C]	:	12																				
Film Properties	:	Clear																				
SAFETY DATA	<p>Health Hazard: ANUCRYL C-764 is alkaline in nature and harmful if swallowed. Avoid contact with skin. Use protective clothing, hand gloves, goggles, safety shoes etc., while handling this material. In case of contact or splash on eyes, wash with sufficient amount of water and consult a physician.</p> <p>Fire Hazard: ANUCRYL C-764 is water-based and non-flammable.</p>																					
STORAGE	Store products in tightly closed original containers at temperatures recommended on the product label.																					
PACKAGING	240 Kg HDPE Drums/Tanker.																					

**HANDLING
PRECAUTION**

Before using this product, consult the Material Safety Data Sheet (MSDS) for details on product hazards, recommended handling precautions and product storage.

DISCLAIMER

This information is given to the best of our knowledge. There is no legally binding assurance of certain properties for a specific purpose. The customer is responsible for determining whether the product and Information provided here is appropriate for his use or not. It is the sole responsibility of the customer to ensure that any proprietary rights and existing laws and legislation are observed.

ANUVI CHEMICALS LIMITED (AN ISO 9001: 2015 COMPANY)

Sales office: 205/210/211, Narmada, Laxmi Industrial Premises,
Pokharan Road No.1, Vartak Nagar, Thane (W) - 400 606,
Maharashtra, India.

Tel.: +91-22-25855379 / 25855714 **Website** www.anuvi.in

