

ANUCRYL C-766

TECHNICAL DATA SHEET

INTRODUCTION	ANUCRYL C- 766 is a styrene/ acrylic emulsion. It gives glossy, UV resistant, flexible film with excellent durability.																					
APPLICATION	ANUCRYL C- 766 is used for glossy Interior and Exterior Paints.																					
TYPICAL PROPERTIES	<table border="0"> <tr> <td>Appearance</td> <td>:</td> <td>Milky white liquid</td> </tr> <tr> <td>% Solid Content</td> <td>:</td> <td>50 ± 1</td> </tr> <tr> <td>pH (As is)</td> <td>:</td> <td>8.0 – 10.0</td> </tr> <tr> <td>Ford Cup Viscosity FCB4</td> <td>:</td> <td>40 -80 seconds</td> </tr> <tr> <td>Glass Transition Temperature</td> <td></td> <td></td> </tr> <tr> <td>Theoretical Tg [°C]</td> <td>:</td> <td>25</td> </tr> <tr> <td>Film formation</td> <td>:</td> <td>Clear</td> </tr> </table>	Appearance	:	Milky white liquid	% Solid Content	:	50 ± 1	pH (As is)	:	8.0 – 10.0	Ford Cup Viscosity FCB4	:	40 -80 seconds	Glass Transition Temperature			Theoretical Tg [°C]	:	25	Film formation	:	Clear
Appearance	:	Milky white liquid																				
% Solid Content	:	50 ± 1																				
pH (As is)	:	8.0 – 10.0																				
Ford Cup Viscosity FCB4	:	40 -80 seconds																				
Glass Transition Temperature																						
Theoretical Tg [°C]	:	25																				
Film formation	:	Clear																				
SAFETY DATA	<p>Health Hazard: ANUCRYL C-766 is alkaline in nature and harmful if swallowed. Avoid contact with skin. Use protective clothing, hand gloves, goggles, safety shoes etc., while handling this material. In case of contact or splash on eyes, wash with sufficient amount of water and consult a physician.</p> <p>Fire Hazard: ANUCRYL C-766 is water-based and non-flammable.</p>																					
STORAGE	Store products in tightly closed original containers at temperatures recommended on the product label.																					
PACKAGING	240 Kg HDPE Drums/Tanker.																					

**HANDLING
PRECAUTION**

Before using this product, consult the Material Safety Data Sheet (MSDS) for details on product hazards, recommended handling precautions and product storage.

DISCLAIMER

This information is given to the best of our knowledge. There is no legally binding assurance of certain properties for a specific purpose. The customer is responsible for determining whether the product and Information provided here is appropriate for his use or not. It is the sole responsibility of the customer to ensure that any proprietary rights and existing laws and legislation are observed.

ANUVI CHEMICALS LIMITED (AN ISO 9001: 2015 COMPANY)

Sales office: 205/210/211, Narmada, Laxmi Industrial Premises,
Pokharan Road No.1, Vartak Nagar, Thane (W) - 400 606,
Maharashtra, India.

Tel.: +91-22-25855379 / 25855714 **Website** www.anuvi.in

