

ANUCRYL CP-200G

TECHNICAL DATA SHEET

INTRODUCTION

ANUCRYL CP-200 G is a silane modified pure acrylic emulsion. It gives UV resistant, transparent, high gloss and hard film. It has good outdoor weatherability and resistance to dirt pick-up.

APPLICATION

ANUCRYL CP-200 G is a Glossy protective coating for Painted Surfaces and Natural stones, Top coat for Multi colour paints

TYPICAL PROPERTIES

Appearance : Translucent liquid

pH (As is) : 8-10 % Solid Content : 35 ± 1

Ford Cup Viscosity @ $30^{\circ c}$ FCB4 : 12 - 16 seconds

Glass Transition Temperature

Theoretical Tg [°C] : 48

SAFETY DATA

Health Hazard: ANUCRYL CP-200G is alkaline in nature and harmful if swallowed. Avoid Contact with skin. Use protective clothing, hand gloves, goggles, safety shoes etc., while handling this material. In case of contact or splash on eyes, wash with sufficient amount of water and consult a physician.

Fire Hazard: ANUCRYL CP-200G is water-based and non-flammable.

STORAGE

Store products in tightly closed original containers at temperatures recommended on the product label.

PACKAGING

240 Kg HDPE Drums/Tanker.

HANDLING PRECAUTION

Before using this product, consult the Material Safety Data Sheet (MSDS) for details onproduct hazards, recommended handling precautions and product storage.

DISCLAIMER

This information is given to the best of our knowledge. There is no legally binding assurance of certain properties for a specific purpose. The customer is responsible for determining whether the product and Information provided here is appropriate for his use or not. It is the sole responsibility of the customer to ensure that any proprietary rights and existing laws and legislation are observed.

ANUVI CHEMICALS LIMITED (AN ISO 9001: 2015 COMPANY)

Sales office: 205/210/211, Narmada, Laxmi Industrial Premises, Pokharan Road No.1, Vartak Nagar, Thane (W) - 400 606,

Maharashtra, India.

Tel.: +91-22-25855379 / 25855714 **Website** <u>www.anuvi.in</u>

