



ANUCRYL K-3232

TECHNICAL DATA SHEET

INTRODUCTION	ANUCRYL K-3232 is an alkaline (polyammonium acrylate) thickener.
APPLICATION	ANUCRYL K-3232 is a neutralized, highly viscous, excellent rheology modifier for paints.
TYPICAL PROPERTIES	Appearance : Clear to slightly hazy solution. % Solid Content : 22 ± 1 pH (2% solid in water) : 8.0 – 10.0 Brook Field Viscosity, Spindle no. 2/ RPM 60@30°C (5% solid in water) : 100 – 170 Cps Thickening action : Excellent
SAFETY DATA	Health Hazard: ANUCRYL K3232 is alkaline in nature and harmful if swallowed. Avoid contact with skin. Use protective clothing, hand gloves, goggles, safety shoes etc., while handling this material. In case of contact or splash on eyes, wash with sufficient amount of water and consult a physician. Fire Hazard: ANUCRYL K-3232 is water-based and non-flammable.
STORAGE	Store products in tightly closed original containers at temperatures recommended on the product label.
PACKAGING	240 Kg HDPE Drums/Tanker.

**HANDLING
PRECAUTION**

Before using this product, consult the Material Safety Data Sheet (MSDS) for details on product hazards, recommended handling precautions and product storage.

DISCLAIMER

This information is given to the best of our knowledge. There is no legally binding assurance of certain properties for a specific purpose. The customer is responsible for determining whether the product and Information provided here is appropriate for his use or not. It is the sole responsibility of the customer to ensure that any proprietary rights and existing laws and legislation are observed.

ANUVI CHEMICALS LIMITED (AN ISO 9001: 2015 COMPANY)

Sales office: 205/210/211, Narmada, Laxmi Industrial Premises,
Pokharan Road No.1, Vartak Nagar, Thane (W) - 400 606,
Maharashtra, India.

Tel.: +91-22-25855379 / 25855714 **Website** www.anuvi.in



