

ANUCRYL T-30

TECHNICAL DATA SHEET

<p>INTRODUCTION</p>	<p>ANUCRYL T-30 is an acrylic based copolymer emulsion for textile industry. Due to its self-cross-linking nature and having excellent emulsifying system, it is an ideal binder for all kinds of printing system. Apart from having extra ordinary mechanical stability, ANUCRYL T-30 gives print of extra fastness on viscose, jute and cotton fabrics</p>										
<p>APPLICATION</p>	<p>ANUCRYL T-30 is successfully used as printing binder for roller and screen-printing operations</p> <p>Recommended Formulation for printing Paste</p> <table border="0"> <tr> <td>Pigment Paste</td> <td>5 Parts by weight</td> </tr> <tr> <td>Anucryl T-30</td> <td>90 Parts by weight</td> </tr> <tr> <td>Anucryl K-116</td> <td>5* Parts by weight</td> </tr> </table> <p>*Should be prepared separately and added to achieve desired paste viscosity</p>	Pigment Paste	5 Parts by weight	Anucryl T-30	90 Parts by weight	Anucryl K-116	5* Parts by weight				
Pigment Paste	5 Parts by weight										
Anucryl T-30	90 Parts by weight										
Anucryl K-116	5* Parts by weight										
<p>TYPICAL PROPERTIES</p>	<table border="0"> <tr> <td>Appearance</td> <td>: Bluish White Liquid</td> </tr> <tr> <td>% Solid Content</td> <td>: 30 ± 1</td> </tr> <tr> <td>B4 Ford Cup Viscosity @30°C</td> <td>: 12-16 Sec</td> </tr> <tr> <td>pH</td> <td>: 7 - 9</td> </tr> <tr> <td>Mechanical Stability</td> <td>: Excellent</td> </tr> </table>	Appearance	: Bluish White Liquid	% Solid Content	: 30 ± 1	B4 Ford Cup Viscosity @30°C	: 12-16 Sec	pH	: 7 - 9	Mechanical Stability	: Excellent
Appearance	: Bluish White Liquid										
% Solid Content	: 30 ± 1										
B4 Ford Cup Viscosity @30°C	: 12-16 Sec										
pH	: 7 - 9										
Mechanical Stability	: Excellent										
<p>SAFETY DATA</p>	<p>Health Hazard: ANUCRYL T-30 is alkaline in nature and harmful if swallowed. Avoid contact with skin. Use protective clothing, hand gloves, goggles, safety shoes etc., while handling this material. In case of contact or splash on eyes, wash with sufficient amount of water and consult a physician.</p> <p>Fire Hazard: ANUCRYL T- 30 is water-based and non-flammable.</p>										

STORAGE	Store products in tightly closed original containers at temperatures recommended on the product label.
PACKAGING	240 Kg HDPE Drums/ Tanker.
HANDLING PRECAUTION	Before using this product, consult the Material Safety Data Sheet (MSDS) for details on product hazards, recommended handling precautions and product storage.
DISCLAIMER	This information is given to the best of our knowledge. There is no legally binding assurance of certain properties for a specific purpose. The customer is responsible for determining whether the product and Information provided here is appropriate for his use or not. It is the sole responsibility of the customer to ensure that any proprietary rights and existing laws and legislation are observed.

ANUVI CHEMICALS LIMITED (AN ISO 9001: 2015 COMPANY)
Sales office: 205/210/211, Narmada, Laxmi Industrial Premises,
Pokharan Road No.1, Vartak Nagar, Than e(W) - 400 606,
Maharashtra, India.
Tel.: +91-22-25855379 / 25855714 **Website** www.anuvi.in



