# Material Safety Data Sheet ANUCRYL W-100MT

DATE OF ISSUE: 01.09.2019 VERSION: / VER 01 / 19

#### SECTION 1. IDENTIFICATION OF THE PRODUCT AND COMPANY/UNDERTAKING

Product Identification : ANUCRYL W-100MT

Details of the supplier and safety data sheet

Company:

Manufacturer/ Supplier : Anuvi Chemicals Limited,

Street / Post Box : 210/211, Narmada, Laxmi

Industrial Premises, Pokhran Road, No.1

Vartak Nagar,

Town / City and Post Code : Thane (West), Maharashtra

Post Code : 400606 Country : India

 Telephone No.
 : +91-22-25855379

 Fax
 : +91-22-25855714

 Email
 : sales@anuvi.in

 Website
 : www.anuvi.in

Emergency contact Number : +91-22-25855714 / +91-251-2690418

#### **SECTION 2. HAZARDOUS IDENTIFICATION**

#### Inhalation

Inhalation of vapour or mist can cause, irritation of nose, throat and lungs.

# Eye contact

Direct contact with material can cause irritation.

# Skin contact

Prolonged or repeated skin contact can cause slight skin irritation.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Sr. No.	Composition	CAS REG. NO.	Effects & Hazards	Weight (%)
1	Co-polymeric emulsion of styrene/ Acrylic	9010-92-8	Non Hazardous	39-41
2	Individual residual monomers		Not required	< 0.1
3	Water	7732-18-5	Non Hazardous	59-61

#### **SECTION 4. FIRST AID MEASURES**

## **Inhalation**

If inhaled send the person in open area. In the event of adverse symptoms take medical treatment.

# **Eye Contact**

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. Seek medical attention if required.

## **Skin contact**

In case of contact with skin wash off immediately with soap and water and consult a doctor if skin irritation persists.

## <u>Ingestio</u>n

If swallowed, give plenty of water to drink. Do not induce vomiting or give anything by mouth, if the person is unconscious. Immediately consult the physician.

#### **SECTION 5. FIRE FIGHTING**

Flash point ->100°C

Auto ignition temperature - Not applicable

Low Explosive Limit - Not applicable

Upper Explosive Limit - Not applicable

## Suitable Extinguishing media

Use extinguishing media suitable to the surrounding fire.

## Fire & Explosion Hazards

Since it is water based, material can splatter above 100°C and dried product (polymer) can burn.

### **Extinguishing Agents**

Suitable extinguishing media: Foam, Carbon Dioxide or Dry powder.

## Personal Protective Equipment

Use hand gloves, Nose mask, safety goggle, safety shoe and apron while using the product.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

#### **Personal Protection**

Appropriate protective equipment must be worn while handling spillage.

#### **Environmental Precautions**

Do not allow to enter drains or waterways

In case of entry into waterways, soil or drains, inform the responsible authorities.

#### **Procedures**

Avoid unnecessary crowd around the affected area. Contain spills by covering it with neutral substances like mud, clay, sand etc. Dispose off the material with neutral substance to safe area or incinerate.

#### **SECTION 7. HANDLING AND STORAGE**

# **Storage Conditions**

Keep material in shade and avoid freezing.

## **Handling Procedures**

Use Proper personal protective equipment's.

Monomer vapours can evaporate when material is subjected to heat during processing operations.

## Additional Information regarding storage

Protect from frost.

Protect from heat and direct sunlight

Protect from atmospheric moisture and water

## **SECTION 8. EXPOSURE CONTROL. / PERSONAL PROTECTION**

Sr. No.	Composition	CAS REG. NO.	Effects & Hazards	Weight (%)
1	Co-polymeric emulsion of styrene/ Acrylic	9010-92-8	Non-Hazardous	39-41
2	Individual residual monomers		Not required	< 0.1
3	Water	7732-18-5	Non-Hazardous	59-61

## General protective and hygiene measures

Take care for sufficient ventilation or exhaust on the workshop place.

Do not eat, drink or smoke during work time.

Wash hands before breaks and after work.

## **Respiratory Protection**

Nose mask Protection

Use air purifying respirators.

# **Eye Protection**

Use safety glasses with side shields.

## **Hand Protection**

Use chemically resistant neoprene type gloves.

## **Engineering Controls**

Use local ventilators.

# **Other Protective Equipment**

Area where this material is stored and used should be equipped with an eyewash facility.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : Translucent liquid

Ford Cup Viscosity @ 30°C FCB4 : 25 – 40 seconds

#### **SECTION 10. STABILITY AND REACTIVITY**

## **Conditions to avoid**

Avoid extreme heat

# **Instability**

This material is stable, however on heating at high temperature polymer decomposes.

## **Hazardous decomposition Products**

Acrylic monomer may come out on thermal decomposition.

## **Hazardous Polymerisation**

The product is chemically stable.

#### **Incompatibility**

There are no known materials which could be incompatible with this product.

#### **SECTION 11 TOXICOLOGICAL INFORMATION**

Oral Mouse LD50 : 3000mg/kg
Oral Rabbit LD50 : 3200mg/kg
Oral Rat LD50 : 1980 mg/kg

#### **SECTION 12. ECOLOGICAL INFORMATION**

## **General Information**

There is no data available for this product.

## **Additional Information**

Due to the high pH, aquatic organism may be harmed. Do not allow to enter waste water Drain, waterways or soil.

#### **SECTION 13. DISPOSAL PROCEDURE**

## Waste treatment methods

Coagulate the emulsion by the stepwise addition of Alum, HCl & caustic lye. Remove the clear supernatant and flush to a chemical sewer. For disposal, incinerate this material at a facility that complies with local and State regulations.

#### **SECTION 14. TRANSPORT INFORMATION**

ADR / RID

Further Information : No dangerous goods.

IMO / IMDG

Further Information : No dangerous goods.

IATA / ICAO

Further Information : No dangerous goods.

#### **SECTION 15. REGULATORY INFORMATION**

Workplace Classification.

This product is non-hazardous.

#### **SECTION 16. OTHER INFORMATION**

Recommended use : Raw material

Suitable for use in industrial sector : Chemical industry

This information is given to the best of our knowledge. There is no legally binding assurance of certain properties for a specific purpose. The customer is responsible for determining whether the product and Information provided here is appropriate for his use. It is the sole responsibility of the customer to ensure that any proprietary rights and existing laws and legislation are observed.

# **ANUVI CHEMICALS LIMITED (AN ISO 9001: 2015 COMPANY)**

**Sales office:** 205/210/211, Narmada, Laxmi Industrial Premises, Pokharan Road No.1, Vartak Nagar, Thane (W) - 400 606, Maharashtra, India.



Tel.: +91-22-25855379 / 25855714