

# IMPRES - 2574

## TECHNICAL DATA SHEET

### INTRODUCTION

IMPRES - 2574 is a high-performance wetting and dispersing agent for inorganic pigments, fillers, TiO<sub>2</sub> and other extenders.

### AREAS OF APPLICATION

IMPRES - 2574 is used as Wetting and Dispersing Agent in water base Inks, pigment paste and dispersions for making inks and Coatings.

### TYPICAL PROPERTIES

Appearance	: Clear to Pale Yellow Liquid
Polymer Type in water	: Acrylic co-polymer solution
% Non-Volatile by wt. @ 150°C for half an hour	: 35 - 37
pH (As is)	: 8.0 – 9.0
Ford-Cup Viscosity @27°C	: Min. 21 sec

### SAFETY DATA

**HEALTH HAZARD:** IMPRES - 2574 is alkaline in nature and harmful if swallowed. Avoid contact with skin and use protective clothing, hand gloves, goggles etc., while handling this material. In case of contact or splash on eyes, wash with copious amount of water and consult a physician.

**FIRE HAZARD:** IMPRES - 2574 is a water-based system and non-flammable.

## DISCLAIMER

The above details have been compiled based on our current knowledge and based on thorough laboratory tests. As the methods and conditions of the use of the products at the printing stage and the further life-cycle thereof is beyond our control, the company accepts no responsibilities / liabilities whatsoever. We suggest that detailed suitability is carried out at the users end.

### **ANUVI CHEMICALS LIMITED (AN ISO 9001: 2015 COMPANY)**

**Sales office:** 205/210/211, Narmada, Laxmi Industrial Premises,  
Pokharan Road No.1, Vartak Nagar, Thane - 400 606,  
Maharashtra. India.

**Tel. :** +91-22-25855379 / 25855714    **Website** [www.anuvi.in](http://www.anuvi.in)



