REF No.:	MSDS/01
Rev. Date:	15/11/15
Issue Date:	31/03/17
Version No.	1

MATERIAL SAFETY DATA SHEET <u>ECO-IMPRES-2077</u>

Product Details					
Description:	Styren	e -Acrylic Emuls	ion		
Product Code/s:	ECO-I	ECO-IMPRES - 2077			
Recommended Use:	For In	dl. (Chem. Ind.)	use only		
Chemical family:	Polym	er			
Company Details					
		Telephone	+91 22 258	+91 22 25855379	
Indl. Premises, Pokhran Rd., Vartak		Fax:	+ 9122 258	+ 9122 2585 5714	
Nagar, Thane		E-Mail: sal		vichem.com	
		Website:	www.anuvichem.com		
Composition / Information	on Ingredie	ents			
Chemical Characterization	1		CAS #	<u>% Range</u>	
Water	-		2 - 18 - 5	45 - 55	
	alia Canalan		1272/2008	40 - 50	
Amine Salt of Modified Acr	упс Сорогуг	IIEI EC	12/2/2000	40 - 30	

Ammonium Hydroxide Alcohols - C11 - C15 secondary, Ethoxylated

Hazards not otherwise Classified: According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

68131 - 40 - 8

Emergency Overview:

Use with local exhaust ventilation. Handle in accordance with good industrial hygiene and safety practice. If used as intended, this product is not expected to present a physical or health hazard.

< 2 %

3. Hazards Identification

Emergency Overview Physical Appearance	Free flowing milky to translucent liquid – Characteristic odour	X
Potential Health Effects		
Eyes	May cause eye burning or irritation on over exposure	
Skin	May cause irritation in the form of redness, burning or dermatitis (last one in severe cases or person being allergic)	The edgest
Ingestion	Chemicals present in this mixture may be harmful if swallowed. Also, may affect nervous system and cause abdominal discomfort.	
Inhalation	May cause moderate respiratory irritation, dizziness, fatigue, nausea & headache	

4. Fin	rst Aid Measures				
Ey		Immediately flush eyes with plenty of water for two to three minutes. Remove eye contact lenses (if wearing one) and continue flushing with water for 15 minutes. Get			
Sk	cin:	medical attention Remove contaminated clothing and immediately wash affected area with plenty of soap and water. Seek medical attention where necessary. Wash contaminated			
In	gestion:	clothing before use. Contact local medical practitioner or medical help. Do not induce vomiting unless advised by medical practitioner. If vomiting occurs then keep head lower than hips			
In	halation:	to help prevent aspiration. Get medical attention immediately. Remove the patient to fresh air (open and airy space), supply oxygen if breathing is difficult. Seek medical attention immediately.			
Cl		Remove contaminated clothing and wash the affected body part/s with water			
5. Fla	ammability & Fire	e Fighting Measures			
Ha pr	xtinguishing media azardous combusti oducts: refighting equipme	 Water spray, Dry Powder and Foam Harmful vapours. Evolution of fumes & fog. Substances / group substances can be released in case of fire. Fire fighters must be equipped with self-contained breathing apparatus and turn-out gear. Contaminated fire extinguishing water must be disposed off in accordance with the official regulations. 			
6. A	ccidental Release	(spillage / leakage) Measures			
G	eneral procedure:	Vacate area of spill or leak. Wear appropriate personal protective equipment. Contain and recover liquid to the extent possible Collect the liquid in an appropriate container or absorb with an inert material like saw dust / dry sand / universal binder / acid binder or cloth stripes (Chindhi) etc. Disperse any vapour and flush spill away from the personnel or other ignitable material. Whatever is collected from the accidental release – treat as prescribed under Disposable Material" Do not discharge in to drains, ground water and/or surface water streams.			
7. Ha	undling & Storage				
Pr	eneral procedure: recautions against l Explosion	No special measures necessary provided product is used correctly Fire No special precaution/s necessary			
in	onditions for storag cluding ay in- ompatibilities	ge, Keep containers tightly closed and in a cool place			
Sł	nelf Life	One year from date of manufacture when stored in original sealed container			

8. Exposure Control & Personal Protection

Exposure guidelines: OSHA Hazardous Components (29 CIR 1910.1200) – Exposure Limits

at recommended storage temperature range.

ANUVI CHEMICAL LTD. ECO-IMPRES-2077

Personal Protection Equipment:

Eye & face Skin

Respiratory:

Wear safety glasses with side shields or goggles when handling this material Wear impervious gloves and appropriate protective clothing as required to minimize contact with skin A half-face organic vapour respirator maybe worn for protection up to ten or fullface respirator for protection up to fifty times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier. Whichever is lowest must be followed. For emergencies where the

exposure levels are unknown, use a full-face air respirator.







9. Physical & Chemical Properties

Physical State % Solid Content Brookfield viscosity cps Spindle 3/RPM 60 at 30°C pН Vapour Density **Boiling Point** Freezing Point Melting Point Solubility in Water Flash Point Flammability Lower explosion limit Upper explosion limit Auto-ignition Density Thermal decomposition VOC or % Volatilities **Evaporation** rate

Semi Translucent liquid 46 ± 1 400 ± 200

 8.0 ± 1 Heavier than air Around 100°C 0°C Not applicable Yes No flash point (measurement made up to boiling point) Not Flammable 15 % (V) 28 % (V) Due to high water content - product does not ignite 1.04 g/cm³ Stable up to boiling point < 1 % Not determined

10. Stability & reactivity

No hazards if stored / handled as prescribed Reactivity Oxidizing properties No fire propagation Chemical Stability Product is stable if product is stored and handled as prescribed. Polymerization or Shall not occur, if product is stored as prescribed Hazardous reactions: Conditions to avoid See sec. 7 (Handling & Storage) No such material identified Incompatible material/s hazards Hazardous decomposition No hazards if stored / handled as prescribed products Thermal decomposition Stable up to boiling point

1. Toxicological Information	
Primary routes of exposure	Routes of entry for solids and liquids are ingestion and inhalation, but
	may include eye or skin contact.
	Routes of entry for gases include inhalation and eye contact.
	Skin contact may be a route of entry for liquefied gases.
Acute Toxicity:	Assessment of acute toxicity: Virtually nontoxic after a single ingestic
	Oral
	Type of value: LD50
	Species: rat
	Value: > 5,000 mg/kg
2. Ecological Information	
Environmental data	No data available.
3. Disposal Considerations	
Product	Material that cannot be transferred to recovery or re-cycle should be
1100000	handled as hazardous waste and the extract disposed off at a Govt.
	Approved waste facility or incinerator (or handed over to waste handl
	authorised contract). Always dispose according to the current regulat
	or the acts of the country of residence.
	Dispose of in accordance with national, state and local regulations. It
	the waste generator's responsibility to determine if a particular waste
	hazardous under RCRA.
Un-cleaned packing:	Contaminated packing material should be emptied as for as possible a
	after appropriate cleaning could be re-used or disposed as per the regulations.
	regulations.
4. Transport Information	
Department of Transport	
Proper Shipping Name	Polymer Emulsion
Technical Name	Acrylic Polymer Emulsion
Land Transport (USDOT)	Not classified as Dangerous Goods under Transport Regulations
Sea Transport (IMDG) Air Transport (IATA / ICA	Not classified as Dangerous Goods under Transport RegulationsNot classified as Dangerous Goods under Transport Regulations
All Hallsport (IATA / ICA	() Not classified as Dangerous Goods under Transport Regulations
5. Regulatory Information	
Federal regulations	
Registration status	Chemical - TSCA US Released list
EPCRA 311/322 Hazard	Acute; Chronic
category	
NFPA Hazard Codes	Health: 1; Fire: 0; Reactivity: 0; Special: None

Health: 1; Fire: 0; Reactivity: 0; Special: None Health: 1; Flammability: 0; Physical hazard: 0

HMIS III Rating

16. Other Information						
	NFPA Codes	Health	1	HMS Codes	Health	1
		Fire	0		Fire	0
		Reactivity	0		Reactivity	0
					Protection	G
Additional Information The OSHA Hazard Communication Standard, 29 CFR 1910.1200, Paragraph (g) (4 specifically permits chemical manufacturers to single MSDS for a category of complex mixtures, where those " Mixtures " have similar Hazards and content Therefore, this MSDS applies to the range of products described in Section 1, or a products with the same product name listed in section 1 (unless described otherwise Where specific data is required for the purposes of regulatory reporting, a Technic. Data Sheet shall be provided for the specific product, on request to u (manufacturer).					gory of ontents. l, or all erwise). chnical	
Manufacturers Disclaimer:Information given herein is offered in good faith as acc Conditions of issue and stability of the product for par the product for specific application/s are beyond our co product are therefore assumed by the user. Nothing is in for uses, which infringe valid Patents or extending I Appropriate warning and safe handling procedures sh handlers and users of this material.			icular use and suitab ntrol; all risks of use ended as a recommen cence under valid I	ility of of this ndation Patents.		

ANUVI CHEMICALS LIMITED (AN ISO 9001: 2015 COMPANY)

Sales office: 205/210/211, Narmada, Laxmi Industrial Premises, Pokharan Road No.1, Vartak Nagar, Thane - 400 606, Maharashtra. India. Tel.: +91-22-25855379 / 25855714 Website: www.anuvi.in

