Material Safety Data Sheet ANUCRYL C-614

DATE OF ISSUE: 01.09.2013 VERSION: / VER 02 / 17 REVISED DATE: 01.02.2017

SECTION 1. IDENTIFICATION OF THE PRODUCT AND COMPANY/UNDERTAKING

Product Identification : ANUCRYL C-614

Details of the supplier and safety data sheet

Company:

Manufacturer/ Supplier : Anuvi Chemicals Limited,
Street / Post Box : 210/211, Narmada, Laxmi

Industrial Premises, Pokhran Road, No.1

Vartak Nagar,

Town / City and Post Code : Thane (West), Maharashtra

Post Code : 400606 Country : India

 Telephone No.
 : +91-22-25855379

 Fax
 : +91-22-25855714

 Email
 : sales@anuvi.in

 Website
 : www.anuvi.in

Emergency contact Number : +91-22-25855714 / +91-251-2690418

SECTION 2. HAZARDOUS IDENTIFICATION

Inhalation

Inhalation of vapour or mist can cause, irritation of nose, throat and lungs.

Eye contact

Direct contact with material can cause irritation.

Skin contact

Prolonged or repeated skin contact can cause slight skin irritation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Sr. No.	Composition	CAS REG. NO.	Effects & Hazards	Weight (%)
1	Copolymer emulsion of Styrene/Acrylic	100-42-5	Non Hazardous	49-51
2	Individual residual monomers		Not required	< 0.1
3	Water	7732-18-5	Non Hazardous	51-49

SECTION 4. FIRST AID MEASURES

Inhalation

If inhaled send the person in open area. In the event of adverse symptoms take medical treatment.

Eye Contact

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. Seek medical attention.

Skin contact

In case of contact with skin wash off immediately with soap and water and consult a doctor if skin irritation persists.

<u>Ingestio</u>n

If swallowed, give plenty of water to drink. Do not induce vomiting or give anything by mouth, if the person is unconscious. Immediately consult the physician.

SECTION 5. FIRE FIGHTING

Flash point ->100°C

Auto ignition temperature - Not applicable

Low Explosive Limit - Not applicable

Upper Explosive Limit - Not applicable

Suitable Extinguishing media

Use extinguishing media suitable to the surrounding fire.

Fire & Explosion Hazards

Since it is water based, material can splatter above 100°C and dried product (polymer) can burn.

Extinguishing Agents

Suitable extinguishing media: Foam, Carbon Dioxide or Dry powder.

Personal Protective Equipment

Use hand gloves, Nose mask, safety goggle, safety shoe and apron while using the product.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Protection

Appropriate protective equipment must be worn while handling spillage.

Environmental Precautions

Do not allow to enter drains or waterways

In case of entry into waterways, soil or drains, inform the responsible authorities.

Procedures

Avoid unnecessary crowd around the affected area. Contain spills by covering it with neutral substances like mud, clay, sand etc. Dispose off the material with neutral substance to safe area or incinerate.

SECTION 7. HANDLING AND STORAGE

Storage Conditions

Keep material in shade and avoid freezing.

Handling Procedures

Use Proper personal protective equipments.

Monomer vapours can evaporate when material is subjected to heat during processing operations.

Additional Information regarding storage

Protect from frost.

Protect from heat and direct sunlight

Protect from atmospheric moisture and water

SECTION 8. EXPOSURE CONTROL. / PERSONAL PROTECTION

Sr. No.	Composition	CAS REG. NO.	Effects & Hazards	Weight (%)
1	Copolymeric emulsion of styrene / acrylic	100-42-5	Non Hazardous	49-51
2	Individual residual monomers		Not required	< 0.1
3	Water	7732-18-5	Non Hazardous	49-51

General protective and hygiene measures

Take care for sufficient ventilation or exhaust on the workshop place.

Do not eat, drink or smoke during work time.

Wash hands before breaks and after work.

Respiratory Protection

Nose mask Protection

Use air purifying respirators.

Eye Protection

Use safety glasses with side shields.

Hand Protection

Use chemically resistant neoprene type gloves.

Engineering Controls

Use local ventilators.

Other Protective Equipment

Area where this material is stored and used should be equipped with an eyewash facility.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Milky white liquid

% Solid Content @150°C 1/2hr : 50 ± 1

pH : 8.0 - 10.0

Brook Field Viscosity : 500-1500 Cps

Spindle No. 3/ RPM 60 @ 30°C

Glass Transition Temperature

Theoretical Tg [°C] : 14
Film properties : Clear

@100 micron

Alkali resistance : Pass
Soft water resistance : Pass
Calcium Chloride test : Pass

SECTION 10. STABILITY AND REACTIVITY

Conditions to avoid

Avoid extreme heat

Instability

This material is stable, however on heating at high temperature polymer decomposes.

Hazardous decomposition Products

Acrylic monomer may come out on thermal decomposition.

Hazardous Polymerisation

The product is chemically stable.

Incompatibility

There are no known materials which could be incompatible with this product.

SECTION 11 TOXICOLOGICAL INFORMATION

 Oral Mouse LD50
 : 3000mg/kg

 Oral Rabbit LD50
 : 3200mg/kg

 Oral Rat LD50
 : 1980 mg/kg

SECTION 12. ECOLOGICAL INFORMATION

General Information

There is no data available for this product.

Additional Information

Due to the high pH, aquatic organism may be harmed. Do not allow to enter waste water Drain, waterways or soil.

SECTION 13. DISPOSAL PROCEDURE

Waste treatment methods

Coagulate the emulsion by the stepwise addition of Alum, HCl & caustic lye. Remove the clear supernatant and flush to a chemical sewer. For disposal, incinerate this material at a facility that complies with local and state regulations.

SECTION 14. TRANSPORT INFORMATION

ADR / RID

Further Information : No dangerous goods.

IMO / IMDG

Further Information : No dangerous goods.

IATA / ICAO

Further Information : No dangerous goods.

SECTION 15. REGULATORY INFORMATION

Workplace Classification.

This product is non-hazardous.

SECTION 16. OTHER INFORMATION

Recommended use : Raw material

Suitable for use in industrial sector : Chemical industry

This information is given to the best of our knowledge. There is no legally binding assurance of certain properties for a specific purpose. The customer is responsible for determining whether the product and Information provided here is appropriate for his use. It is the sole responsibility of the customer to ensure that any proprietary rights and existing laws and legislation are observed.

ANUVI CHEMICALS LIMITED (AN ISO 9001: 2015 COMPANY)

Sales office: 205/210/211, Narmada, Laxmi Industrial Premises,

Pokharan Road No.1, Vartak Nagar, Thane (W) - 400 606,

Maharashtra, India.

Tel.: +91-22-25855379 / 25855714

